

1025USBC-LB

Double switched socket + USB charger, Clipsal Solis T Series, horizontal, USB C type, 10A, living brass



Main

| | |
|---------------------------|----------------------------------|
| Product or component type | Switched socket with USB charger |
| Assembly Type | Complete product |
| Standards | AS/NZS 3112 |
| Product certifications | RCM |
| Main colour tint | Living brass |

Complementary

| | |
|--------------------------------|----------------------------------------------------------------------------------|
| Range | Clipsal Solis T Series |
| Number Of Outlets | 2 |
| Device mounting | Wall mounted 65 mm |
| Cover type | With shutter |
| Number of power socket outlets | 2 x 2P + E, Australian/New Zealand |
| Rated current | 10 A 230/240 V, AC, 50 Hz |
| Connections - terminals | 4 x 2.5 mm ² screw terminals 3 x 4 mm ² screw terminals |
| Colour tint | Living brass |
| Surface finish | Brass finish |
| Surface treatment | Metallic |
| Additional Function | USB type C |
| Material | Brass |
| Screwdriver shape | Philips No 2 Square drive no 1 (SQ1) |
| Wire stripping length | 16 mm |
| Fixing mode | By screw |
| Fixing center | 120 mm |
| Height | 74 mm |
| Width | 148 mm |
| Depth | 68.9 mm |
| Sale per indivisible quantity | 1 |
| Installation Type | Flush |
| Installation Orientation | Horizontal |
| Control type | Rocker |
| Cover Thickness | 3.9 mm |
| Cut-out dimensions | 130 x 50 mm |
| Number Of Switches | 2 |

Environment

| | |
|---------------------------------------|-----------|
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 15.5 cm |
| Package 1 Width | 8 cm |
| Package 1 Length | 8 cm |
| Package 1 Weight | 328 g |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 30 |
| Package 2 Height | 32.5 cm |
| Package 2 Width | 25 cm |
| Package 2 Length | 41 cm |
| Package 2 Weight | 10.22 kg |

Offer Sustainability

| | |
|----------------------------|----------------------------------------|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |