

Product data sheet

Characteristics

1042TA-PT

Switch, Clipsal Solis T Series, 2 gangs, horizontal, 16AX/20A, platinum



Main

Range	Clipsal Solis T Series
Product brand	Clipsal
Product or component type	Switch
Assembly Type	Complete product
Outlet standard deviation	Australian/New Zealand
Colour tint	Platinum

Complementary

Number of gangs	2 gangs
[Ue] rated operational voltage	230/240 V
Network type	AC
Network frequency	50 Hz
Rated current	20 A/16 AX
Control type	Toggle switch
Connections - terminals	Screw terminals
Installation Type	Flush
Number Of Switches	2
Material	Aluminium
Installation direction	Horizontal
Surface treatment	Metallic
Load type	LEDi lamp 0...250 W 20 A/16 AX
Terminals Capacity	4 x 1.5...3 x 2.5 mm ²
Screwdriver shape	Phillips No 2 Square drive no 1 (SQ1)
Wire stripping length	10 mm
Mounting Type	Screw
Cover Thickness	3.6 mm
Mounting Centers	84 mm
Cut-out dimensions	93 x 50 mm
Product certifications	RCM
Surface finish	Aluminium
Height	74 mm
Width	148 mm
Depth	56 mm
Embedding depth	41 mm
Motor M-rating AS3133	M80
Switch function	1-pole 1/2-way

Environment

Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Standards	AS/NZS 60669

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	8 cm
Package 1 Length	8 cm
Package 1 Weight	100 g
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Height	34 cm
Package 2 Width	36 cm
Package 2 Length	48 cm
Package 2 Weight	3.084 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes