

Product data sheet

Characteristics

CPL7600ATP-WE

Fan, Light and Heater units, Airflow, LED (downlight), 7W, 45dB, white



Main

Range of product	Airflow
Range	Airflow
Product brand	Clipsal
Product destination	Ceiling fitting
Device application	Duct
Main colour tint	White
Colour tint	White

Complementary

[Ue] rated operational voltage	230/240 V AC 50 Hz
Air flow	300 m3/h
Power consumption in W	590 W
Depth	200 mm
Air discharge option	Downflow
Noise level	45 dB
Fan type	Centrifugal
Light source	LED 7 W
Heat dissipation	275 W

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43 cm
Package 1 Width	33 cm
Package 1 Length	53.7 cm
Package 1 Weight	6.3 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	12
Package 2 Height	110 cm
Package 2 Width	114 cm
Package 2 Length	114 cm
Package 2 Weight	90.6 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins