



Data Cables – Overall Screened

Application:	Internal and external inter-connections of electronic apparatus such as computers, intercoms, signalling and alarm systems.
Conductor:	Tinned Annealed Copper Wire
Insulation:	Multi-Core – PVC V-75, Multi-Pair - Polypropylene
Screen:	Aluminium Tape Screen, Polyester Mylar Tape lapping and Tinned Copper Drain Wire.
Sheath:	PVC 4V-75
Voltage:	240V Radial Thickness Sheath
Standards:	AS1125 (Conductor), AS/NZS 3808 (PVC)
Greenstar:	Approved

NOT TO BE CONNECTED TO MAINS

Multi-Core

ELECTRA Part Number	CORES	SIZE	O.D.
EAS7204	4	0.22	4.8
EAS7206	6	0.22	5.7
EAS7208	8	0.22	6.3
EAS7210	10	0.22	7.0
EAS7212	12	0.22	7.4

*O.D. \pm 10% = mm *Size = mm²

Multi-Pair

ELECTRA Part Number	PAIRS	SIZE	O.D.
EAS7201P	1	0.22	4.2
EAS7201PHV*	1	0.22	4.8
EAS7202P	2	0.22	5.7
EAS7203P	3	0.22	5.9
EAS7204P	4	0.22	6.4
EAS7206P	6	0.22	7.5
EAS7208P	8	0.22	8.6
EAS7210P	10	0.22	9.7
EAS7212P	12	0.22	10.3

*(PHV) 0.6/1kV Insulation Radial *O.D. \pm 10% = mm *Size = mm

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38