



ANOVA S9105 - 4W

Compact 4 watt recessed LED cabinet luminaire

Application

Ideal for any residential or commercial interior space

Design Specifications

- Durable die-cast aluminium body profile
- White powder coat or satin nickel plated finish
- High efficiency LED optics
- CCT choice of 3000K / 4000K / 6000K
- 12V DC LED driver required, suitable drivers - PLUTO
EGL12V/6W, PLUTO 15DV, 40DV, 60DV

Performance

- Dimmable - **NO**



Technical Specification



Product	Model No.	Input Voltage (V/DC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	S9105WW/WH	12	4	280	3000	80
	S9105CW/WH	12	4	280	4000	80
	S9105DL/WH	12	4	280	6000	80
	S9105WW/SN	12	4	280	3000	80
	S9105DL/SN	12	4	280	6000	80
	S9105CW/SN	12	4	280	4000	80

Beam Angle (°)	Dimmable	Diameter (mm)	Dim (mm)	Cut Out (mm)	Body Colour
90	NO	70	15(H)	60	WHITE
90	NO	70	15(H)	60	WHITE
90	NO	70	15(H)	60	WHITE
90	NO	70	15(H)	60	SATIN NICKEL
90	NO	70	15(H)	60	SATIN NICKEL
90	NO	70	15(H)	60	SATIN NICKEL

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

S9105



Ø59mm



Photometric Data

Unit: cd C0/C180 — C90/C270 —

S9105WW ST at 3000K

