

Product data sheet

Characteristics

CLITPDB1200

LED Diffused Batten, Clipsal - Lighting, 36W, 600mm, 4500lm, white

Main

Range	Clipsal
Product name	TPDB Series
Product or component type	Batten light
Device application	Lighting
Market segment	Small commercial Residential

Complementary

Type of installation	Indoor/outdoor
Total system power	36 W
Light source	LED 36 W
[Ue] rated operational voltage	230/240 V AC 50 Hz
Luminous flux	4500 lm
Bulb lifespan	50000 h
Colour temperature	3000 K 4000 K 5000 K
Device mounting	Surface
Mounting mode	Surface mounting
IP degree of protection	IP20
IK degree of protection	IK02
Electrical insulation class	Class I
Length	1200 mm
Width	70 mm
Height	68 mm
Shape	Rectangular
Net weight	1550 g

Environment

Colour rendering index	R _a =80
Ambient air temperature for operation	-10...45 °C
Relative humidity	10...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	7.6 cm
Package 1 Length	123.3 cm
Package 1 Weight	1.862 kg

Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Height	18.5 cm
Package 2 Width	17.4 cm
Package 2 Length	131.5 cm
Package 2 Weight	8.14 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	120
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	135 cm
Package 3 Weight	267.2 kg

Offer Sustainability

Packaging without single use plastic	No
Packaging made with recycled cardboard	No
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product
Take-back	No
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	336

Contractual warranty

Warranty	3 years
----------	---------