

Product data sheet Characteristics

WHC363-RG

Switch, Weathershield, 1-Gang, 3 Pole, 63A, 415VAC, IP66



Main

Range of product	Weathershield
Product brand	Clipsal
Assembly Type	Basic element with complete housing

Complementary

Number of poles	3
Installation Type	Surface
Local signalling	without
[Ue] rated operational voltage	415 V AC
Rated current	63 A
Marking	ON-OFF
Marking location	Marking on surface
Mounting Type	By screws
Surface finish	Brilliant
Switch function	3-pole

Environment

Standards	AS 60529 AS/NZS 60947-3
	IEC 60669-1 AS/NZS 3947-3:approval number S/1

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	13.5 cm	
Package 1 Width	12.0 cm	
Package 1 Length	23.8 cm	
Package 1 Weight	1269.6 g	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

•		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	

Life Is On